



HF6 1.8KW


BATTERY CHARGER

PBM Group

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

pbmbatterychargers.com

P.B.M. Srl
Via Barella Z.I.
41058 Vignola (Modena) ITALY

 +39 059 7705311

 info@gruppopbm.it



- ▶ High frequency battery charger with efficiency > 90%
- ▶ 8 Charge profiles
- ▶ Signals of error code anomalies
- ▶ High energy saving
- ▶ Single phase input supply 230VAC ±10% 50/60 Hz
- ▶ Visualization on a LCD display: Curve set, Current (A), Battery voltage (U), Time of charging (h)
- ▶ Ah charged (Ah), Signals of anomalies, Error code
- ▶ Possibility to change the charging curve by external dipswitch, choosing from 8 pre-programmed curves for lead-acid, GEL, AGM batteries

BATTERY CHARGER

MODEL

HF6 1.8KW

Model	Ah Battery		Mains
	7 ÷ 8 h	10 ÷ 12 h	
24V / 60A	360÷420	480÷600	230Vac
24V / 70A	420÷490	560÷700	230Vac
36V / 40A	240÷280	320÷400	230Vac
36V / 45A	270÷315	360÷450	230Vac
48V / 30A	180÷210	240÷300	230Vac
48V / 35A	210÷245	280÷350	230Vac
72V / 22A	132÷154	176÷220	230Vac
80V / 20A	120÷140	160÷200	230Vac