



## SMART UP PLUS


BATTERY MONITORING

### PBM Group

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

[pbmbatterychargers.com](http://pbmbatterychargers.com)

P.B.M. Srl  
Via Barella Z.I.  
41058 Vignola (Modena) ITALY

 +39 059 7705311

 [info@gruppopbm.it](mailto:info@gruppopbm.it)



- ▶ Battery Monitoring devices
- ▶ Data Memory 400 working cycles
- ▶ For batteries 24/36/48/72/80/96V (12V available on request)
- ▶ Hall effect sensor
- ▶ Discharge time and capacity
- ▶ Battery faults and failures occurring during the charging process
- ▶ Temperature indication available on SMARTUP Plus
- ▶ Low electrolyte level available on SMARTUP Plus
- ▶ USB Flash memory for data downloading
- ▶ USB Cable for programming
- ▶ IP54 Protection
- ▶ Working temperature -20° to + 50°

BATTERY MONITORING

MODEL

**SMART UP** PLUS

Model	Ah Battery
Smart-UP Plus T200	100 ÷ 340
Smart-UP Plus T400	350 ÷ 740
Smart-UP Plus T800	750 ÷ 1500