



TL

BATTERY CHARGER




PBM *Group*

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

pbmbatterychargers.com

P.B.M. Srl
Via Barella Z.I.
41058 Vignola (Modena) ITALY

 +39 059 7705311

 info@gruppopbm.it

PAG. 1 di 1



- ▶ Single-phase input supply 120/208/240 VAC, Frequency 60 Hz
- ▶ Different power supply voltages available on request
- ▶ Transformer adjustments to $\pm 5\%$ VAC
- ▶ Tropicalized stray-flux transformer, copper windings with double enamel insulation, class H, impregnated with non-toxic resins, kiln-dried
- ▶ Overload cutout on transformer
- ▶ Rectifier bridge equipped with interference suppressing filters
- ▶ Protection fuses on mains input and D.C. output
- ▶ Complete with mains and battery cables, assembly of plugs and battery connectors on request

BATTERY CHARGER

MODEL

TL

<i>Model</i>	<i>Ah Battery 8 ÷ 9 h</i>	<i>Mains voltage</i>
12V / 20A	100 ÷ 120	120/208/240
12V / 30A	150 ÷ 180	
12V / 40A	200 ÷ 240	
12V / 50A	250 ÷ 300	
12V / 60A	300 ÷ 360	
24V / 20A	100 ÷ 120	120/208/240
24V / 30A	150 ÷ 180	
24V / 40A	200 ÷ 240	
24V / 50A	250 ÷ 300	
36V / 20A	100 ÷ 120	120/208/240
36V / 30A	150 ÷ 180	
36V / 40A	200 ÷ 240	
48V / 20A	100 ÷ 120	120/208/240
48V / 30A	150 ÷ 180	